



AMPLINK™

POWER DISTRIBUTION MODULE

Rowe Electronics, Inc
515-981-5504
info@rowe-electronics.com

NEW PRODUCT

- **60 Amp total capacity**
- **6 High current 20A outputs**
- **Programmable amp limits**
- **Output over current monitoring**
- **Rugged and waterproof**
- **Wireless control and setup**
- **Battery tender circuit**
- **3 programmable Input triggers**
- **Free Amplink App**



New from Rowe Electronics, Amplink PDM. Built on the strong reputation of the original PDM60, the Amplink PDM maintains the total current capacity of 60 amps over 6 outputs. Each output is monitored and will shut down in the event of a short or over current fault. You can now program and view the system status on your phone using Bluetooth. Solid state electronics are used in the Amplink PDM for more reliability, less wires and more control of your power.

Specifications

- Operating Voltage: 6-24V for 12V systems
- Total Current Capacity: 60 Amp maximum continuous
- Outputs: 6 (20A) High side outputs
- Inputs: 3 configurable inputs
- Operating Temperature: -40 to 185°F
- Communication: Bluetooth (LE) 4.1
- Fully sealed 18 inch hardwire leads
- Water Protection: Fully encapsulated waterproof
- Weight: 10 oz
- Dimensions: 3.00 x 2.00 x 0.90 in.

Proven Technology By Rowe Electronics